PRO1 SUBMITTAL SHEET

Job Name: _____ **Location:** _____ **Date:** _____

Purchaser: _____ **Installer:** _____

Submitted to: _____ **For:** ☐ RNC ☐ R&R ☐ Commercial

MODEL T855

Universal
Light Commercial / Residential

Up to 2 Heat, 2 Cool Conventional
Up to 3 Heat, 2 Cool Heat Pump
Battery or Hardwire
7 Day, 5/1/1 or Non-Programmable



This model features:

- 8 sq. inch display
- Blue backlight
- Glow in the dark light button
- Easy access battery compartment
- Keypad lockout
- Adjustable setpoint limits
- Simple private label badge system
- Easy access battery compartment
- Auto changeover (*Not available in PTAC mode)
- 5 Year Warranty
- Seperate heating and cooling swing (cycle rate) adjustments
- 5 minute compressor delay protection (selectable on or off)
- Universal subbase
- Battery or 24v power
- Programmable Fan

Specifications:

Application	Up to 2 Heat, 2 Cool Conventional - Up to 3 Heat, 2 Cool Heat Pump
Programmability	7 Day, 5/1/1 or Non-Programmable
Changeover	Auto
Display Range	41˚F to 95˚F (5˚C to 35˚C)
Control Range	44˚F to 90˚F (7˚C to 32˚C)
Display Accuracy	+/- 1˚F
Heat Swing	Adjustable from 0.2˚F to 2.0˚F
Cool Swing	Adjustable from 0.2˚F to 2.0˚F
Terminals	Rc, Rh, G, Y, Y2, C, O, B, W/E, W2
Load Rating	1 amp per terminal, 1.5 amp maximum all terminals combined
Power Source	18 to 30 VAC, NEC Class II, 50/60 Hz for hardwire (common wire) Battery power from 2 AA Alkaline batteries
Operating Ambient	32˚F to +105˚F (0˚C to +41˚C)
Operating Humidity	90% non-condensing maximum
Mounting	Wall or Junction Box
Dimensions	4.7”W x 4.4”H x 1.1”D (119mm W x 112mm H x 28mm D)
Warranty	5 year warranty